

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET
60Hz/1800 rpm/3.3kV/4.16kV



MGS1000HV

60Hz/3.3kV/4.16kV

POWER RATING (0.8 P.F.)	MODEL CODE
STAND-BY 1070 kW	63S/64S-T62M
PRIME 960 kW	63P/64P-T62M



MGS1000HV with typical options

CONDITIONS & DEFINITIONS

Stand-by: Code: S

Applicable for supplying emergency power at varying load in the event of the normal utility power interruption.
Fuel stop power in accordance with ISO15550, ISO3046/1, JISB8002-1, DIN6271 and BS5514.
Overload: not allowed

Prime: Code: P

Applicable for supplying emergency power at varying load in the event of normal utility power interruption. + 10% overload in accordance with ISO3046/1. Overload power in accordance with ISO15550, ISO3046/1, JIS8002-1, DIN6271 and BS5514.

Conditions:

Engine ratings are based on SAE J1349 standard conditions and also apply at ISO3046/1, DIN6271 & BS5514 standard conditions.

Fuel rates: based on ASTM D975, BS2869 and on fuel oil of 35° API (16°C or 60° F) gravity having a LHV of 42,780 kJ/kg (18,390 Btu/lb.) when used at 29°C (85° F) and weighing 838.9 g/liter (7.001lbs./U.S. gal.).

Note: * Please consult with your nearest Mitsubishi MGS dealer for additional rating requirements.

DIMENSION (Reference Data)

			STAND-BY	PRIME
			1070 kW	960 kW
Overall dimensions	L : Length	mm	4635	4635
	W : Width	mm	1920	1920
	H : Height	mm	2360	2360
Total Weight (Dry)		kg	9200	9200
Total Weight (Wet)		kg	9670	9670

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET
MGS1000HV



MGS SERIES DIESEL ENGINE: MITSUBISHI S12H-PTA-S

V-12, 4 stroke-cycle water-cooled, turbocharged and aftercooled

ENGINE SPECIFICATIONS & TECHNICAL DATA

Bore	mm	150
Stroke	mm	175
Displacement	L	37.11
Piston speed	m/sec.	10.5
Compression ratio		14.0
Lubricating oil capacity	L	200
Coolant capacity without/with radiator	L	100/231
Coolant pump external resistance	m water	3.5
Coolant pump flow rate	L/min	1450
Cooling fan airflow rate	m ³ /min	1800
Cooling fan air flow restriction	kPa	0.1
Ambient air temperature	°C	40
Allowable exhaust back pressure	kPa	6.0
Exhaust flange size (internal diameter)	mm	200

ENGINE OPERATING DATA

		STAND-BY 1070 kW	PRIME 960 kW
Gross Engine Power*	kWm	1136	1029
Brake mean effective pressure	MPa	2.1	1.9
Regenerative absorption	kW	108	108
Noise Level at 1 m (excluding: intake, exhaust & fan)	dB(A)	114	112
Fuel consumption load 100%*	L/hr.	295	267
Fuel consumption load 75%*	L/hr.	228	208
Combustion air inlet flow rate	m ³ /min	105	95
Exhaust gas flow rate	m ³ /min	278	251
Exhaust gas temperature	°C	510	510
Heat rejection to coolant	kW	767	693
Heat rejection to exhaust	kW	1032	926
Heat rejection to atmosphere from engine	kW	92	83
Heat rejection to atmosphere from generator	kW	68	61

* WITH FAN basis.

Deration for engine

Note: Please consult with your nearest Mitsubishi MGS dealer

ENGINE STANDARD EQUIPMENT

Aftercooler
Turbocharger filter (For MGS-B, HV stand-by and prime)
Paper element type filter (For MGS-C, HV PRP continuous)
Structure steel base
Crankcase breather
Charging alternator
Lubricating oil cooler
Fuel filters, full flow paper element
Fuel transfer pump, gear driven, plunger type
Electronic type governor
Jacket water heater *
Jacket water pump, gear driven
Lubricating oil filter, full flow paper element
Lubricating oil pump, gear driven
Exhaust dry manifold
Radiator, blower fan, fan drive
Manual shutoff
24V DC electric starting motor

* Depending on the model, it becomes optional setting.

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET
MGS1000HV



MGS SERIES 7310 MK II GENERATOR CONTROL PANEL

Features

MGS standard 7310 MK II programmable microprocessor generator control panel provides the following functions

- ◆ Start and stop control
- ◆ Engine and generator measurement items on LCD display and LED on the front panel for operation status indication
- ◆ Engine and generator shutdown and warning protection
- ◆ Generator breaker control
- ◆ Expansion module for additional output and input
- ◆ RS485 and RS232C communication for remote monitoring

Mounting

Fabricated cubicle mounted on individual bracket with anti-vibration isolator

Instrument and control accessories

- Generator running indicator
- Manual button
- Auto button
- CB open button (Manual only)
- CB close button (Manual only)
- Manual start button
- Manual Stop/Reset button
- Selector switch (ACTIVE, PANEL LOCK, STOP/RESET)
- Mute alarm button
- Menu navigation button
- Common alarm indicator
- Voltage adjuster
- Speed adjuster
- Emergency stop pushbutton

Measured items on LCD display

- Generator volts L1-N, L2-N, L3-N
- Generator volts L1-L2, L2-L3, L3-L1
- Generator amps L1, L2, L3
- Generator Frequency Hz
- Engine speed RPM
- Engine oil pressure (PSI & Bar & kPa)
- Engine cooling water temperature (°C & °F)
- Battery volts
- Engine hours run
- Generator Load kW, kVA, kVar
- Generator Load kWh, kVAh, kVarh
- Power Factor
- Generator Phase Sequence

Shutdown and Warning items on LCD display

- High coolant temperature : shutdown and warning
- Low oil pressure : shutdown and warning
- Fail to start : shutdown
- Over-speed : shutdown and warning
- Under-speed : shutdown and warning
- Loss of speed signal : shutdown
- Fail to stop : warning
- Over voltage (DC) : warning
- Under voltage (DC) : warning
- Lubrication oil filter clogged : warning
- High oil temperature : shutdown and warning *1 *2
- Oil pressure sender open circuit : shutdown
- Charge fail : warning
- Exhaust gas temperature high : warning *1
- Coolant level low : warning *1
- High crankcase internal pressure : shutdown *1
- Generator high current : shutdown (IDMT) and warning
- Over voltage (AC) : shutdown and warning
- Under voltage (AC) : shutdown and warning
- Over frequency : warning
- Under frequency : warning
- Overload : warning
- Winding temperature high (U, V, W) : warning *1
- Bearing temperature high : warning *1
- Electrical trip
- Emergency stop : shutdown

*1 : MGS-C, HV continuous are applicable as standard. The others are applicable as option.

*2 : MGS2700 and MGS2800 are applicable as standard. The others are applicable as option.

Operation status indicated by LED

- Remote start present
- Generator ready
- Lubrication oil filter clogged
- Electrical trip

MITSUBISHI MGS SERIES

DIESEL GENERATOR SET
MGS1000HV



MGS SERIES AC GENERATOR MODEL: MG-KT62M

Features

MGS original design, single bearing, 4 pole, screen protected, self excited, self regulating and brushless with fully connected damper windings, salient pole rotors, A.C. exciter and rotating rectifier unit. Direct coupled to engine and greasable bearing, direct drive centrifugal blower.

With Space heater.

Enclosure: Drip-proof IP23

Terminal box: Totally enclosed IP44

Winding System

Standard 6 wire winding is provided. All windings are formed wound and impregnated in vacuum pressure with a special epoxy resin.

Overspeed capability: 125% for 2 minutes

Insulation: Class 'H'

Temperature rise: 150°C(Stand-by),125°C(Prime)

Voltage Regulator

Fully sealed, 3 phase RMS sensing AVR with built-in protection against sustained over-excitation.

Voltage regulation: Less than +/- 0.5% from no load to full load at any power factor between 0.8 lagging and 1.0 allowing for a 4% engine speed variation

Voltage adjustment: +/- 6%

Wave form: Less than 5% deviation

Permanent Magnet Generator (PMG)

Separately excited system which provide isolated power supply for the AVR – sustain short circuit current approximately 250-300% under fault condition.

Sensors

Temperature sensors are provided as follows.

Stator winding, 2 per each phase, PT100

Bearing, PT100

*Generator winding and bearing temperature indication Meters are option.

Electrical Design

In accordance with ISO 8528-3, IEC60034-1/BS EN60034-1, BS5000 Part 3, VDE0530, NEMA MG1-32, CSA22-2-100 and AS1359.

Telephone Influence Factor (TIF): Less than 50

Gen Set Option Features

■ ENGINE

Air Cleaner, paper element dry type
(For MGS-B, HV stand-by and prime only)
Battery Kit
Battery Charger
Anchor Bolts

■ FUEL

Fuel Day Service Tank

■ COOLING

Oversize radiator
Heat Exchanger
Expansion Tank
Removal STD Radiator, Fan & Fan Drive

■ LUBRICATION

Lub. Oil Level Regulator

■ EXHAUST

Exhaust Silencer
Exhaust Flexible Pipe

■ GENERATOR

Power Factor Regulator

■ CONTROL PANEL

Diesel Generator Integrated Communication Synthesizer
(DGICS-MII)
Auxiliary Control Panel

Remote Monitor Interface

2157 expansion unit (Output signal module)

2130 expansion unit (Input signal module)

2133 expansion unit (RTD/Thermocouple input module)

■ SWITCHGEAR

Circuit Breaker MCCB & ACB

Reverse Power Relay



No. 3, Tuas Avenue 12, Singapore 639024
Republic of Singapore
Phone:65-6862 2202 Fax: 65-6862 5728
URL: <http://www.mhiesa.com/>

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001:2015 =

Mitsubishi Heavy Industries Engine System Asia Pte Ltd, serves for the customers with improved products continually.
Therefore specification and some materials will be changed without notice.
The International System of units (SI) is used in this publication.